

Product Name: 3D Matrix Booster

Description: Autotriz 3D Matrix Booster can be used as a cost saving measure to help protect your paint by sealing the surface with a micro-thin layer of protection infused with Polysilazane technology.



Coverage: 3D Matrix Booster is particularly suitable for car painted surfaces, such as one (1K) or two component (2K) paints (polyurethane or epoxy systems), plastic & trims, glass, wheels, chrome, stainless steel surface. The preferred use is for the exterior paint of cars, motorbikes, trucks, and buses. It can be used on top of any coated surface as a top up layer.

Technical Data		General Data	
Shelf life	12 months	Product Category	3D Matrix Booster
Appearance	Colorless	Volume	Automotive Coating
Curing	Normal ambient	Application	300ML (AT-BS-300)
Base	Polysilazane	Coverage	Vehicle Exterior
Specified Gravity	0.86 g/cm ³	Storage	300ML (30m ² - 36m ²)
Hazard	Non-Hazardous		5-35°C/41-95°F
Properties		Tools Needed	
<ul style="list-style-type: none"> • Easy on, easy off • Standalone/Top-up layer • Ultra-smooth surface • Easy-to-clean • Polysilazane formula • Super hydrophobic effect • Easy to apply • Child-safe (non-toxic formula) • Environmental friendly 		<ul style="list-style-type: none"> • Pressure spray applicator • Lint-free microfiber towel (AT-AC-MC) 	

Guide: The product is for professional use and should be applied by approved applicators only. Test on a small area or apply a test coat before application.

Instruction: Shake well before use. Get ready with 2 pieces of brand new, lint-free microfiber towel. (It is recommended that new towels to be rinsed or washed with water prior to use to reduce the loosing lint). It is recommended to do a 2 ft. x 4 ft. area or 4 ft. x 4 ft. at a time. Spray on 3D Matrix Booster on surface. Wait for 30 seconds (time is vary from different countries and different season depending on temperature or humidity, ask distributors for recommendation), use first towel to remove the product. Go immediately over with second microfiber towel with polishing motion until the surface is free from residue. When the whole car is applied, allow curing of 1-2 hours.

Precaution: Product is supplied with a cap and trigger sprayer nozzle separately. Always tighten the bottle with cap after every use. Trigger sprayer nozzle should be emptied and air dried for next use to avoid blockage.

Process and Curing: The product must be applied at an ambient temperature of at least + 5°C and relative humidity of 30 % - 80 %. Avoid direct sunlight! Apply the coating in clean and dry conditions. Any mistakes can be rectified within approx. 5 min of application. Traces of water in the applicator should also be avoided. Applicators dampened with water should not be used. 3D Matrix Booster is dry-to-touch after about one hour. The 3D Matrix Booster is fully effective after 1-2 hours of curing at room temperature. During this time, the vehicles should not be driven into a vehicle wash.