

Product Name: Glass Cut Compound

Description: AUTOTRIZ Glass Cut Compound is a high quality,

one-step polishing compound for safe removal of severe water spots and light scratches on glass surfaces. AUTOTRIZ Glass Cut Compound is a cutting-edge solution for glass correction with a blend of aluminium oxide and cerium oxide mineral. Ensures good clarity and the highest level of driving safety possible. Contains no wax, silicones, fillers or glazing oils which makes it great

to use prior to applying windscreen or glass coating. Body shop safe.



Technical Data		General Data	
Appearance	Cream	Product	Glass Cut Compound
Cut	6/10	Group	Polishing
Gloss	>10	Category	Alternative
Speed	Alternative	Volume	1L (AT-PC-GC-1)
Pressure	Moderate	Application	Windscreen/Window
Abrasive effect	Water spot removal	Complimentary	Wool/Foam Pad
Specified Gravity	1.18 g/cm ³	Industries	Detailing/Paint shops
Hazard	Non-Hazardous	Storage	5-35°C/41-95°F

Directions: Shake bottle well before use. Clean the glass thoroughly. Work on a cool and

> clean surface. Cover the panels and rubber seals with masking tape. Apply small amount on the AUTOTRIZ Glass Polish Wool Pad or a Wool Applicator Block. Add a fine mist of water. Use rectangular sander, rotary or DA polisher to buff thoroughly over the entire glass surface until desired result is achieved. Rinse the surface with water. Wipe off with microfiber towel and

do inspection. If necessary, repeat the process for any defect.

Tips: Add fine mist of water to act as lubricating agent when product dries out.