

Product Name: Extreme Cut 801

Description: Highly abrasive polishing paste for fast defect removal. For restoration of weathered and scratched paint. Removes up to P1500 sanding marks. Removes sanding marks, scratches, and heavy swirls from all types of paint. Silicone free and low dusting.



Technical Data		General Data	
Appearance	Cream	Product	Extreme Cut 801
Cut	8/10	Group	Polishing
Gloss	>5	Category	Alternative
Speed	Alternative	Volume	1L (AT-PC-801)
Pressure	Moderate	Application	Body Paint
Abrasive effect	Scratch removal	Complimentary	Wool/Foam Pad
Specified Gravity	1.21 g/cm ³	Industries	Detailing/Paint shops
Hazard	Non-Hazardous	Storage	5-35°C/41-95°F

Directions: Shake bottle well before use. Work on a cool and clean surface.

DA Application: Apply product to the AUTOTRIZ Medium Cut Wool Pad (AT-WP-MC), or Medium Cut Foam Pad (AT-FP-MC), or Fine Cut Foam Pad (AT-FP-FC). Set machine speed to 4-5, Apply moderate to light pressure with 3-5 overlapping passes until desired cutting result is achieved.

Rotary Application: Set rotary polisher speed to 1500-2000RPM. Use AUTOTRIZ Heavy Cut Wool Pad (AT-WP-HC) or Medium Cut Foam Pad (AT-FP-MC). Apply product on paint surface directly, work on 2'x2' area at each time. Apply moderate to light pressure with 3-5 overlapping passes until scratches and sanding marks are removed.

Removes residue with a AUTOTRIZ Microfiber Cloth Ultrafine (AT-MT40). For final polishing, use AUTOTRIZ Supreme Polish (AT-PC-402).

Tips: Clean pads frequently. Use AUTOTRIZ Surface Prep (AT-CC-SP) to remove residue and check for any defect.