

Product Name: Heavy Cut 901

Description: AUTOTRIZ Heavy Cut 901 is recommended for use on OEM and refinish paint systems to reliably cut P1500 or finer sanding marks, while leaving a swirl free, high gloss finish with reduced product consumption. It is the only compound that minimizes process speed by completing both the cutting and polishing steps with one product. AUTOTRIZ Heavy Cut 901 is mostly suitable for all modern paint systems. Contains no fillers and silicone.



Technical Data		General Data	
Appearance	Cream	Product	Heavy Cut 901
Cut	9/10	Group	Polishing
Gloss	>4	Category	Alternative
Speed	Alternative	Volume	1L (AT-PC9-901)
Pressure	Moderate	Application	Body Paint
Abrasive effect	Scratch removal	Complimentary	Wool/Foam Pad
Specified Gravity	1.22 g/cm ³	Industries	Detailing/Paint shops
Hazard	Non-Hazardous	Storage	5-35°C/41-95°F

Directions: Shake bottle well before use. Work on a cool and clean surface.

Rotary Application: Set rotary polisher speed to 1500-2000RPM. Use AUTOTRIZ Heavy Cut Wool Pad (AT-WP-20) or Heavy Cut Foam Pad (AT-FP-HC). Apply product on paint surface directly, work on 2'x2' area at each time. Apply moderate to light pressure with 3-5 overlapping passes until scratches and sanding marks are removed.

Removes residue with a AUTOTRIZ Microfiber Cloth Ultrafine (AT-MT-40). For medium compounding, use AUTOTRIZ Final Cut (AT-PC-601). For final finishing, use AUTOTRIZ Supreme Polish (AT-PC402) or AUTOTRIZ Ultimate Polish (AT-PC-302).

Tips: Clean pads frequently. Use AUTOTRIZ Surface Prep (AT-CC-SP) to remove residue and check for any defect.