

Product Name: Supreme Polish 402

Description: The standard high-gloss polish is effective in the removal of compounding marks to produce deep, wet, mirror-like reflections with high gloss. AUTOTRIZ Supreme Polish 402 adds depth of colour, especially on dark-colored cars, leaving a swirl-free finish. Wax and Silicone free formula.



Technical Data		General Data	
Appearance	Cream	Product	Supreme Polish 402
Cut	4/10	Group	Polishing
Gloss	>9	Category	Alternative
Speed	Alternative	Volume	1L (AT-PC-402)
Pressure	Moderate	Application	Body Paint
Abrasive effect	Hologram removal	Complimentary	Wool/Foam Pad
Specified Gravity	1.20 g/cm ³	Industries	Detailing/Paint shops
Hazard	Non-Hazardous	Storage	5-35°C/41-95°F

Directions: Shake bottle well before use. Work on a cool and clean surface.

DA Application: Apply product to the AUTOTRIZ Medium Cut Wool Pad (AT-WP-MC), or Medium Cut Foam Pad (AT-FP-MC), or Fine Cut Foam Pad (AT-FP-FC). Set machine speed to 4-5, Apply moderate to light pressure with 3-5 overlapping passes until desired cutting result is achieved.

Rotary Application: Set rotary polisher speed to 1500-2000RPM. Use AUTOTRIZ Heavy Cut Wool Pad (AT-WP-20) or Fine Cut Wool Pad (AT-WP-30). Apply product on paint surface directly, work on 2'x2' area at each time. Apply moderate to light pressure with 3-5 overlapping passes until scratches and sanding marks are removed.

Removes residue with a AUTOTRIZ Microfiber Cloth Ultrafine (AT-MT40). For medium compounding, use AUTOTRIZ Final Cut (AT-PC-601). For final finishing, use AUTOTRIZ Ultimate Polish (AT-PC-302).

Tips: Clean pads frequently. Use AUTOTRIZ Surface Prep (AT-CC-SP) to remove residue and check for any defect.