

Product Name: PPF Gel

Description: AUTOTRIZ PPF Gel is a premixed Paint Protection installation aid designed to support the application of paint protection film. The gel facilitates the ease of application keeping the substrate well moisturized providing the right tack and positioning of the film during installation. This thick and viscous Gel allows the product to be sprayed on the car without dripping off or evaporating quickly. The Gel residues can be easily cleaned after application, even when fully dried.



Directions: Dilute to required specifications and apply to desired surface. Dwell for 30-45 seconds and thoroughly rinse clean with water. DO NOT LET DRY ON SURFACE.

Precaution: Do not breathe dust/fume/gas/mist/vapors/spray. Get medical advice/attention if you feel unwell. KEEP OUT OF REACH OF CHILDREN.

First Aid: Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Skin Contact: If symptoms occur, wash with water. Call a poison center or doctor if irritation develops or persists. Wash off with soap and plenty of water. Consult a physician. Ingestion: Call a poison center or doctor if you feel unwell. If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration. Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Inhalation: Call a poison center or doctor if you feel unwell. If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.



| Technical Data | | General Data | |
|--------------------------|------------------------|--------------------|-------------------|
| Flash Point | 100°C | Product | PPF Gel |
| Appearance | Translucent White | Category | Surface Prep |
| Physical State | Liquid | Volume | 4L (AT-PPF-IG- 4) |
| Odour | Floral smell | Application | PPF Installation |
| Specified Gravity | 0.98 g/cm ³ | Storage | 5-35°C/41-95°F |
| Hazard | Non-Hazardous | | |

