

Product Name: Leather & Vinyl

Description: Autotriz Leather & Vinyl is suitable for all type of leather, synthetic leather/ vinyl and plastic parts. It leaves a long-lasting barrier to protect the surface against permanent stains from dye of blue jeans, pen or marker. Unlike oil based or water-based leather dressings on the market that only leave a temporary dressing, Autotriz Leather & Vinyl preserves the natural feel of leather with its non-oily and non-slippery finish.



Coverage: Leather & Vinyl Coating is particularly suitable for genuine leather & vinyl surface, interior trim, dashboard, door panel, steering wheel and gear knob.

Technical Data		General Data	
Shelf life	12 months	Product Category	Leather & Vinyl
Appearance	Colorless	Volume	Automotive Coating
Curing	Normal ambient	Application	50ML (AT-V6-50)
Base	Organic Polysilazane	Coverage	Leather & Vinyl Parts
Specified Gravity	0.95 g/cm ³	Storage	50ML (3m ² - 5m ²)
Hazard	Non-Hazardous		5-35°C/41-95°F
Properties		Tools Needed	
<ul style="list-style-type: none"> • Non-greasy • Non-slippery • Dark matte finish • Solvent and wear resistant • Protect against permanent staining • Excellent chemical resistance • Prevent pen and marker pen inks • Protects from food & drinks staining • Protects from jean dyes 		<ul style="list-style-type: none"> • Lint-free microfiber towel (AT-AC-MC) • Puff applicator (AT-AC-PA) 	

Guide: The product is for professional use and should be applied by approved applicators only. Test on a small area or apply a test coat before application.

Instruction: Clean the surface thoroughly. Apply Leather & Vinyl Coating with puff applicator using normal pressure with horizontal and vertical movement. If there is any residue, remove it using a microfiber cloth lightly. Wait 1 hour before adding an additional layer. A second layer will enhance the protection. When finished. Keep the treated surface away from water and dirt for the next 2 hours.

Precaution: Make sure the surface is completely clean. Product beads or “fish eyes” is a sign of a silicone release agent or dressing has been used on the surface.

Process

and Curing: The product must be applied at an ambient temperature of at least + 5°C and relative humidity of 30 % - 80 %. Avoid direct sunlight! Apply the coating in clean and dry conditions. Any mistakes can be rectified within approx. 10 min of application. Traces of water in the applicator should also be avoided. Applicators dampened with water should not be used. The applicators cannot be reused once the coating has been applied. Leather & Vinyl Coating is dry-to-touch after about one hour.